


# Crosby® Kuplex®

## Components




### Crosby KUPLEX Pipe Hook KPH

For lifting pipes. Used in pairs.

Crosby Stock No.	Type/Size Reference	WLL (t)		Dimensions (mm)				Weight (kg)
		8	8+10	R	A	D	S	
2781467	KPH10	3.2	4	238	82	45	25	3.06

Note: Sling rated at minimum 30° from the vertical (60° included angle).  
**MUST BE USED IN PAIRS.**




### Crosby KUPLEX Bale Hook KB

For handling soft bales such as wood pulp, scrap paper, etc. Used in pairs.

Crosby Stock No.	Type/Size Reference	WLL (t)		Dimensions (mm)			Weight (kg)
		8	8+10	R	D	T	
2781476	KB7	1.5	2	191	22	70	.85

### Crosby KUPLEX Drum Hook KD


For lifting steel drums. Used in pairs.



Crosby Stock No.	Type/Size Reference	WLL (t)		Dimensions (mm)		Weight (kg)
		8	8+10	R	A	
2781485	KD7	1.5	2	150	28	.93

Note: Sling rated at minimum 30° from the vertical (60° included angle).  
**MUST BE USED IN PAIRS.**

## Lashing Equipment



### Crosby KUPLEX Grab Hook KG

The narrow throat is intended to engage one link of chain. The preferred use is in lashing chain and similar assemblies.

It is not suitable for slinging applications and should never be used for shortening sling legs.

Crosby Stock No.	Reference	WLL (t)		Dimensions (mm)				Weight (kg)
		8	8+10	R	D	S	T	
2781494	KG7N	1.5	2	51	22	14	9	.23
2781500	KG10N	3.2	4	79	31	17	12	.69
2781519	KG13N	5.3	6.7	102	41	22	16	1.54
2781528	KG16N	8	10	124	50	27	20	2.71



### Crosby KUPLEX Turnbuckle KTB

For chain tensioning in load lashings and anchorages. NOT TO BE USED FOR LIFTING PURPOSES.

Crosby Stock No.	Type/Size Reference	WLL (t)		Dimensions (mm)		Weight (kg)
		8	8+10	R Min.	R Max.	
2781537	KTB10	3.2	4	375	611	2.36
2781546	KTB13	5.3	6.7	400	616	3.63